

ISOMETRIC VIEW

NOTES: UNLESS OTHERWISE SPECIFIED.

- 1. ALL DIMENSIONS ARE IN DECIMAL INCHES.
- 2. PRE-CAST CONCRETE MATERIALS AND MANUFACTURING METHODS SHALL CONFORM TO ASTM C-478.
- 3. CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH F C= 4000 PSI AT 28 DAYS.
- 4. THE PORTLAND CEMENT USED IN THE PRE-CAST SECTIONS SHALL MEET THE REQUIREMENTS OF TYPE V HIGH SULFATE RESISTANT CEMENT IN ACCORDANCE WITH ASTM C-150.
- 5. PRE-CAST JOINTS SHALL BE SEALED USING TYLOX® SUPERSEAL™ OR BY USING A DOUBLE LAYER OF KENT SEAL OR RAM-NEK.
- OPTIONAL: PIPE TO MANHOLE CONNECTIONS SHALL BE MADE USING X-CEL, A-LOK OR Z-LOK FLEXIBLE CONNECTORS BY A-LOK PRODUCTS. CONNECTORS SHALL MEET THE REQUIREMENTS OF ASTM C-923
- 7. CONTRACTOR SHALL SEAL ALL PENETRATIONS MADE AT JOB SITE AND OR NOT SHOWN ON PLANS.
- 8. INTERIOR OF PRE-CAST SHAFTS AND LID SHALL BE LINED WITH AMERON T-LOCK. ALL MATERIALS AND INSTALLATION SHALL BE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- 9. ACCESS COVER PER SEPARATE SUBMITTAL.
- EXTERIOR WATER PROOFING SHALL BE W R GRACE BITUTHENE 4000.
 WATER PROOFING SHALL BE APPLIED TO EXTERIOR OF SHAFT SECTIONS
 IN THE FACTORY. LIFTING POINTS TO BE SEALED BY CONTRACTOR AFTER
 ERECTION.
- 11. FILLET IS CONSTRUCTED AS A SECONDARY POUR IN THE FACTORY. THE ANNULAR SPACE BETWEEN FILLET AND SHAFTING SHALL BE FILLED WITH GROUT AFTER ASSEMBLY IN FIELD. FILLET IS NOT LINED OR COATED.
- 12. PUMPS, PIPING AND HARDWARE BY OTHERS.




TITLE


PUMP STATION, 120.00 DIA

 APPROVED BY
 DATE
 DRAWN BY
 DATE
 MODEL NO.

 F. ANSALDI
 12/14/2005
 PS120-STD
 SH 1 OF 4



TOP VIEW



PUMP STATION VIEW

Phone (805) 527-0841 Fax (805) 584-0769

PUMP STATION, 120.00 DIA

DRAWN BY APPROVED BY APPROVED BY MODEL NO. F. ANSALDI 12/14/2005

PS120-STD H:\MH\PS_Std-Catalog\PS120-STD.idw

SH 2 OF 4

