



ID	А	В	С	D	Е	F	G	WALL TYPE	D-LOAD CLASS	STEEL INNER/OUTER	WEIGHT
48"	8'-1 1/4"	7'-9"	5'-3 1/2"	4'-11 1/2"	7 3/4"	2"	5 3/4"	С	Ш	.16 .10	6,900 lbs
48"	8'-1 1/4"	7'-9"	5'-3 1/2"	4'-11 1/2"	7 3/4"	2"	5 3/4"	С	IV	.26 .16	6,900 lbs
48"	8'-1 1/4"	7'-9"	5'-3 1/2"	4'-11 1/2"	7 3/4"	2"	5 3/4"	С	V	.47 .27	6,900 lbs

<sup>\*</sup> STEEL USED WILL MEET OR EXCEED ASTM C76





## Notes

- 1. ALL DIMENSIONS SUBJECT TO ALLOWABLE SPECIFICATION TOLERANCES AND PARAMETERS.
- 2. STEEL WWM ASTM A-1064, REINFORCING TO MEET AND/OR EXCEED ASTM-C76.
- 3. PIPE IS MANUFACTURED PER ASTM C-76, AND CONFORMS TO 2018 CALTRANS STANDARD SPECIFICATION SECTION 65-2 REINFORCED CONCRETE PIPE.
- 4. INTERNAL RUBBER GASKET SHALL CONFORM TO AASHTO DESIGNATION M-198-75 AND ASTM C-443
- 5. CONCRETE F'c = 6000 PSI @ 28 DAYS



THE CONTENTS OF THESE DRAWINGS
ARE THE PROPERTY OF PRECON PRODUCTS
AND ARE PRORIETARY AND CONFIDENTIAL.
THESE DOCUMENTS SHALL NOT BE
DISSMINATED FOR ANY OTHER USE,
WITHOUT THE WRITTHEN CONSENT OF
PRECON PRODUCYS. IF YOU RECEIVE
THESE DRAWINGS IN ERROR, RETURN
TO SENDER WITHOUT READING, COPYING
OR DISCLOSING THE CONTENTS.

DRAWN BY:
W.Tack
DATE:

6/9/2021

48" x 8' RCP RG

SHEETS:

DO NOT SCALE

- ALL DIMENSIONS SUBJECT TO ALLOWABLE SPECIFICATION TOLERANCES AND PARAMETERS.
- 2. STEEL WWM ASTM A-1064, REINFORCING TO MEET AND/OR EXCEED ASTM-C76.
- 3. PIPE IS MANUFACTURED PER ASTM C-76, AND CONFORMS TO 2018 CALTRANS STANDARD SPECIFICATION SECTION 65-2 REINFORCED CONCRETE PIPE.
- 4. INTERNAL RUBBER GASKET SHALL CONFORM TO AASHTO DESIGNATION M-198-75 AND ASTM C-443 5. CONCRETE F'c = 6000 PSI @ 28 DAYS



THE CONTENTS OF THESE DRAWINGS
ARE THE PROPERTY OF PRECON PRODUCTS
AND ARE PRORIETARY AND CONFIDENTIAL.
THESE DOCUMENTS SHALL NOT BE
DISSMINATED FOR ANY OTHER USE,
WITHOUT THE WRITTHEN CONSENT OF
PRECON PRODUCYS. IF YOU RECEIVE
THESE DRAWINGS IN ERROR, RETURN
TO SENDER WITHOUT READING, COPYING
OR DISCLOSING THE CONTENTS.

DRAWN BY: W.Tack DATE: 6/9/2021

48" RCP RG JOINT DETAIL SHEETS: 2 OF 2

DO NOT SCALE